



Temperature range:

Refrigerating unit:

Refrigerant/Cooling factor:

Specifications	BALI 1.0-mod/C	BALI 1.0-mod/C	BALI 1.6-mod/C	BALI 1.9-mod/C	BALI 2.5-mod/C
CODE	BL100-c	BL101-c	BL102-c	BL103-c	BL104-c
Length [mm]	920	1230	1530	1840	2460
Capacity [dm ³]	610	810	1010	1220	1630
Cooling area of shelves [m ²]	2	2,7	3,4	4,1	5,5
Depth [mm]	725	725	725	725	725
Height [mm]	2020+/-10	2020+/-10	2020+/-10	2020+/-10	2020+/-10
Unit weight [kg]	115	145	175	215	255
Refrigerant/Cooling factor	R404A / R507	R404A / R507	R404A / R507	R404A / R507	R404A / R507
Evaporating temperature [°C]	-10	-10	-10	-10	-10
Cooling power demand [W/mb]	800	800	800	800	800
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	28,8	34	44,8	57,6	68
Rated power [W]	73	100	133	146	178
Electricity consumption [kWh/24h]	1	1,4	1,9	2	2,5

Standard equipment

device prepared for multiplexing

dynamic cooling (ventilated)

insulated plastic sides with insulated glass - selectable colour (IGLOO colour chart)

ecological polyurethane foam insulation

base and front panel made of colored coated steel - different colors available (Igloo pattern book)

top panel illuminated with LED light - different plexiglass colors available (IGLOO pattern book)

additional internal top illumination - LED lamp (color of choice: white, confectionery or meaty "deep pink")

interior and exposition shelves made of coated steel - different colors available (Igloo pattern book)

exposition shelves with height and angle adjustment

price stripes - different colors available (IGLOO pattern book)

bumper - different colors available (IGLOO pattern book)

night roller blind

automatic defrost

electronic temperature controller with digital display (IGLOO)

Options

device without side panels prepared for multiplexing (MOD/A)

self - closing sliding doors with combined glass

hinged doors with combined glass

insulated plastic sides with insulated glass - selectable colour (IGLOO colour chart)

side panels made of double combined tempered glass or double combined mirror

insulated side panels made of white coated steel - thickness : 40 mm

customizable colour of side panels made of coated steel (contact the Igloo sales department)

insulated side panels made of stainless steel

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

custom front panel color (after consultation with the IGLOO Sales Department)

front panel color - different colors available (IGLOO pattern book)

base and front panel made of white coated steel (contact the Igloo sales department)

top full panel made of stainless steel

top wooden panel - different colors available (IGLOO pattern book)

wooden bumper - different colors available (IGLOO pattern book)

custom colors of device interior and exposition shelves

device interior and exposition shelves made of stainless steel

device interior and exposition shelves made of acid - resistant stainless steel

strengthening of full shelves

good securing fence

internal, upper lighting - LED lamp (color of choice: white, confectionery or meaty "deep pink")

top mirrors

meat hooks - long

powder painted evaporator

automatic defrost

fixed partition made of PETG (plexiglass)

electronic temperature recorder + software

recorder cable

top outlets of the cooling circuitry

BALI MOD C

