



Temperature range: **+1°C/+10°C**

Refrigerating unit: **External**

Refrigerant/Cooling factor: **R404A / R507**

Specifications	KING 1.0 AT	KING 1.3 AT	KING 1.6 AT	KING 1.9 AT	KING 2.5 AT
CODE	KG100AT-c	KG101AT-c	KG102AT-c	KG103AT-c	KG104AT-c
Length of the module without sides [mm]	920	1230	1530	1840	2460
Capacity [dm <sup>3</sup> ]	748	966	1208	1449	1944
Working capacity of the chamber [dm <sup>3</sup> ]	748	966	1208	1449	1944
The area of shelves [m <sup>2</sup> ]	2,8	3,7	4,6	5,5	7,4
Side panel thickness [mm]	40	40	40	40	40
Depth [mm]	770	770	770	770	770
Height [mm]	2170+/10	2170+/10	2170+/10	2170+/10	2170+/10
Internal height [mm]	1635	1635	1635	1635	1635
Refrigerant/Cooling factor	R404A / R507	R404A / R507	R404A / R507	R404A / R507	R404A / R507
Evaporating temperature [°C]	-10	-10	-10	-10	-10
Cooling power demand [W/m <sup>2</sup> ]	1000	1000	1000	1000	1000
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	28,8	34	45,3	57,6	57,6
Rated power [W]	92	119	130	165	197
Electricity consumption [kWh/24h]	1,3	1,7	1,8	2,3	2,8

## Standard equipment

powered only by external aggregate

device prepared for multiplexing

dynamic cooling (ventilated)

ecological polyurethane foam insulation

front bottom panel made of coated steel - different colors available (Igloo pattern book)

front panel made of painted steel - different colors available (IGLOO pattern book)

additional internal top illumination - LED lamp (color of choice: white, confectionery or meaty "deep pink")

interior and exposition shelves made of coated steel - different colors available (Igloo pattern book)

6 levels of display shelves with possibility to change the hanging height and angle + lower base shelf

price stripes - different colors available (IGLOO pattern book)

night roller blind

automatic defrost

---

automatic condensate pump (up to 0,6m height)

---

electronic temperature controller with digital display (IGLOO)

---

## Options

insulated side panels made of white coated steel - thickness : 40 mm

---

device without side panels prepared for multiplexing (MOD/A)

---

self - closing sliding doors with combined glass

---

insulated side panels made of white coated steel - thickness : 40 mm

---

glass in side panels

---

side panels made of double combined tempered glass or double combined mirror

---

custom colors of the side panels

---

insulated side panels made of stainless steel

---

custom front panel color (after consultation with the IGLOO Sales Department)

---

front panel color - different colors available (IGLOO pattern book)

---

base and front panel made of white coated steel (contact the Igloo sales department)

---

top full panel made of stainless steel

---

bumper - different colors available (IGLOO pattern book)

---

custom colors of device interior and exposition shelves

---

device interior and exposition shelves made of stainless steel

---

device interior and exposition shelves made of acid - resistant stainless steel

---

strengthening of full shelves

---

good securing fence

---

internal, upper lighting - LED lamp (color of choice: white, confectionery or meaty "deep pink")

---

top mirrors

---

meat hooks - long

---

powder painted evaporator

---

automatic defrost

---

fixed partition made of PETG (plexiglass)

---

electronic temperature recorder + software

---

recorder cable

---

top outlets of the cooling circuitry

---

KING AT MOD/C

